



EPON OLT FD1002S CLI User Manual

(V1.2)

Shenzhen C-Data Technology Co., Ltd.

www.cdatatec.com

Contents

1.	Preface	5
1.1.	Introduction	5
1.2.	Definition.....	5
2.	Configuration Preparation	6
2.1.	Management Model.....	6
2.2.	Console Port Connection.....	6
2.3.	Network Connection	7
2.4.	User Login EPON CLI System	7
3.	Command Format Illustration	8
3.1.	Command Format	8
3.2.	Typical Parameter Category.....	9
4.	System Root Directory	11
4.1.	Enable System Log Printed to Super Terminal.....	11
4.2.	System Debug Mode	12
4.2.1.	debug.....	12
4.2.2.	dump	12
4.2.3.	log-lvl	13
4.3.	Enable Mode	13
4.3.1.	Switch Control Module MAC Address Management.....	14
4.3.1.1.	Configure switch control module's MAC Aging Time	14
4.3.1.2.	Show switch control module's MAC Address List	14
4.3.2.	Port mirror Management	14
4.3.2.1.	Mirror Destination Port	14
4.3.2.2.	Add Mirror Source Port	15
4.3.2.3.	Delete Mirror Source Port	15
4.3.2.4.	Clear Mirror Source	15
4.3.3.	Network Configuration Mode	16
4.3.3.1.	Configure Management Port's IP and Sub Mask.....	16
4.3.3.2.	Configure NMS Port Gateway.....	17
4.3.4.	OLT Management Mode.....	17
4.3.4.1.	Enter OLT Management Mode	17
4.3.4.2.	Enable OLT	18
4.3.4.3.	OLT Bridge Configuration.....	18
4.3.4.4.	Restore PON Default Setting.....	20
4.3.4.5.	Link Management Mode	21
4.3.4.6.	ONU Management Mode	27
4.3.4.7.	Configure Link ID Overwrite Function	40
4.3.4.8.	Configure ONU ID Overwrite Function	40
4.3.4.9.	Reboot PON Card.....	40
4.3.4.10.	Save PON card configuration	41
4.3.4.11.	Show OLT's Basic Information.....	41

4.3.5.	Configure Enable Password Management	41
4.3.6.	RSTP Configuration Mode	42
4.3.6.1.	Configure RSTP Bridge Parameter	42
4.3.6.2.	Enable RSTP Function	43
4.3.6.3.	Disable RSTP Function	44
4.3.6.4.	Hold Bridge Forwarding Frame Count	44
4.3.6.5.	Configure RSTP Port Parameter	44
4.3.6.6.	Show RSTP Configuration Information	46
4.3.7.	Configure switch control module's Switching Mode	47
4.3.7.1.	Set Private Vlan Mode	47
4.3.7.2.	Show switch control module's Switch Mode Configuration	47
4.3.7.3.	Enable switch control module's Vlan Function.....	47
4.3.8.	Uplink Port Management mode of switch control module.....	48
4.3.8.1.	Set Port's RX Frames Types.....	49
4.3.8.2.	Set Port's Default Priority Level.....	49
4.3.8.3.	Configure Port's Duplex Mode	49
4.3.8.4.	Enable Port	50
4.3.8.5.	Disable Port	50
4.3.8.6.	Configure Port's Flow Control Mode	50
4.3.8.7.	Set Port's RX Filter Function	50
4.3.8.8.	Configure Port Mode	51
4.3.8.9.	Enable Port's Nest-Vlan Function	51
4.3.8.10.	Enable Port's Protocol Vlan	51
4.3.8.11.	Set Port's PVID.....	52
4.3.8.12.	Configure Port's Rate Limits	52
4.3.8.13.	Configure Port's Reauto-Negotiation Function	52
4.3.8.14.	Show Port Information	52
4.3.8.15.	Configure Port's Compulsive Shutdown Function	53
4.3.8.16.	Remove Compulsive Shutdown Port	53
4.3.8.17.	Configure Current Port Rate	53
4.3.9.	System Configuration Mode.....	54
4.3.10.	Synchrony with ONU Configuration	54
4.3.10.1.	Backup EPON System Configuration.....	55
4.3.10.2.	Restore EPON System Configuration	55
4.3.10.3.	Configure Console Port Speed.....	55
4.3.10.4.	ONU Authorization Management Mode	56
4.3.10.5.	Set SNMP Read Community	58
4.3.10.6.	Reboot OLT	58
4.3.10.7.	Restore Default Configuration and Reboot Equipment.....	59
4.3.10.8.	Save Current Configuration	60
4.3.10.9.	Set Trap Receiving IP Address.....	60
4.3.10.10.	Set SNMP Written Community	60
4.3.11.	Trunk Management Mode.....	61
4.3.11.1.	Configure Trunk Balance Algorithm.....	61

4.3.11.2.	Delete Trunk Group	62
4.3.11.3.	Add Trunk Member	62
4.3.12.	Show Trunk Configuration Information	62
4.3.13.	User Management.....	63
4.3.13.1.	Set User Authority	63
4.3.13.2.	Add User	63
4.3.13.3.	Delete User	63
4.3.13.4.	Change User Password	64
4.3.13.5.	Show Current User's Information	64
4.3.13.6.	Change User's Timeout	64
4.3.14.	VLAN Management Mode.....	65
4.3.14.1.	Delete Vlan Member	65
4.3.14.2.	Delete Vlan	66
4.3.14.3.	Add Vlan Member Port list	66
4.3.15.	Show Vlan Configuration Information	66
4.4.	Show System Running Information	68
4.4.1.	Show System's Current CPU Running Status	68
4.4.2.	Show System's Memory Use Status.....	68
4.4.3.	Show System's Task Status	69
4.4.4.	Enable CATV (RF) Function	69
4.4.5.	disable CATV (RF) Cut-Off Function	70
4.5.	Global Command.....	70
4.5.1.	Create Command Alias	70
4.5.2.	Change Directory.....	70
4.5.3.	Clear Screen.....	70
4.5.4.	Copy File.....	71
4.5.5.	Show System's Date.....	71
4.5.6.	Delete File	71
4.5.7.	Exit From The Current Command Mode	71
4.5.8.	Return to System Main Directory	72
4.5.9.	Help	72
4.5.10.	Command History.....	72
4.5.11.	Log Out System.....	72
4.5.12.	Show Current File List.....	72
4.5.13.	PING.....	73
4.5.14.	Show Directory Route.....	73
4.5.15.	TFTP	73

1. Preface

1.1. Introduction


C-Data OLT FD2000S system could support inband and outband network management mode and EMS network management based on SNMP , which we would provide our EMS software along with the parcel for shipping .Besides, we could also support CLI management for user to get access to our EPON system with more option. Herein ,we would like to introduce our CLE user manual .However ,we would still highly recommend users to use our EMS management to monitor and configure the whole EPON system via EMS since we have offered very powerful function and simple operation in the EMS interface .

1.2. Definition

Product/Abbreviation	Description
EPON	Gigabit Ethernet Passive Optical Network
OLT	Optical Line Terminal
ONU	Optical Network Unit


2. Configuration Preparation

2.1. Management Model



2.2. Console Port Connection

There is a Console port in the front panel of switch control module .The command line configuration interface is enabled via console port connecting to the NMS's superior terminal .Super terminal's basic configuration is as follows :



2.3. Network Connection

FD2100S support inband management (CAT5 connect to ge1-ge8 port) and outband management (CAT4 cable to management port).After Telnet to CLI interface ,we can manage the EPON products.

Default outband network management IP:192.168.120.100

Default inband network management IP: 192.168.1.100

2.4. User Login EPON CLI System

System provide two login accounts default as follows:

User	Password
admin	Admin
guest	Blank

After you log in successfully, the following interface pops up :

```

*****
Command Line Interface for EPON System
Hardware Ver: OLT-0.2
    
```

```

Software Ver: OLT-1.5.2
Created Date: Sep 30 2013 17:02:11
Copyright (c) 2006-2012 . All rights reserved.
*****
Login:admin
Password:
epon>

```

When the command lines shows : epon> ,user can input the configuration command to mangle or inquire the configuration information .

3. Command Format Illustration

3.1. Command Format

- 1 Command Conventions
- 2 Keyboard Operation Conventions
- 3 Symbols

Convention	Description
Boldface	Used to highlight the key words (important words that should never be modified when input).
<i>italic</i>	Used to denote the parameters that should be replaced by actual values when practical use in command line.
[]	Items(keywords or arguments) in square brackets [] are optional.
(x y ...)	Alternative items are grouped in braces and separated by vertical bars. One is selected.
[x y ...]	Optional alternative items are grouped in square brackets and separated by vertical bars. One or none is selected.
<x-y>	Values range from x to y. One is selected.
\$	A line starting with the \$ sign is comments.

Format	Description
<key>	Press the key with the key name inside angle brackets. For example, <Enter>, <Tab>, <Backspace>, or <A>.

<key1 + key2>	Press the keys concurrently. For example, <Ctrl+Alt+A> means the three keys should be pressed concurrently.
<key1, key2>	Press the keys in turn. For example, <Alt, A> means the two keys should be pressed in turn.

Eye-catching symbols are also used in the manual to highlight the points worthy of special attention during the operation. They are defined as follow:



Caution: Means reader be extremely careful. Improper operation may cause data loss or damage to equipment



Warning: Means reader be extremely careful. Improper operation may cause bodily injury.



Note: Means a complementary description.

4. Hints Commands in this manual is case sensitive.

3.2. Typical Parameter Category

When configure the system with CLI(command lines) ,we will meet with some data types with fixed format ,which embody some index's meaning ,expression mode and value range.

Herein,we list some repeated commands to explain their meaning and use.

vlanid	Vlan index with valid integer value from 1 to 4094 .
port	Port number including gigabitethernet ports from 1 to 6, short for ge1 to ge6 . <i>To mention that ge5 to ge6 can't be seen, corresponding with 2 PON ports .We can say that ge5~ge6 is for PON1-PON2 configuration. While ge1~ge4 is for switch control modul's 4 uplink port configuration.</i>
portlist	Port list such as "ge1,ge5"(2 ports) ,"ge1-ge5"(meaning 5 ports from ge1 to ge5.)
ifx-name	Ip port name includes inband and outband.inband interfaces is

	embodied with vi+number (vi means virtual interface).for example: "vi0" means the first inband IP interface(it's the only one interface to support inband ip interface.);outband interface is embody with "cpm+number".cpm is the outband interface's device name .For example, cmp0 means the first outband ip nterface .(this is the only one interface to support outband ip interface .)																																																														
ip-addr	Ip address such as 192.168.1.1																																																														
ip-mask	Ip mask with 4 segments of algorism bytes ,such as 255.255.255.0																																																														
mac	MAC address such as 00:01:02:02:04:05																																																														
moduleid	<p>Module ID number</p> <table border="1"> <thead> <tr> <th>moduleid</th> <th>module name</th> </tr> </thead> <tbody> <tr><td>3</td><td>common mbuf pool</td></tr> <tr><td>4</td><td>HDLC driver</td></tr> <tr><td>5</td><td>inter-board communicaiton protocol</td></tr> <tr><td>9</td><td>device online status maintenance</td></tr> <tr><td>10</td><td>system basic configuration</td></tr> <tr><td>11</td><td>user manager</td></tr> <tr><td>12</td><td>switch port attribute management</td></tr> <tr><td>13</td><td>switch port status poll task</td></tr> <tr><td>14</td><td>switch port statistics poll task</td></tr> <tr><td>15</td><td>trunk module</td></tr> <tr><td>16</td><td>mirroring module</td></tr> <tr><td>17</td><td>normal vlan module</td></tr> <tr><td>18</td><td>protocol type based VLAN</td></tr> <tr><td>19</td><td>rapid spanning tree module</td></tr> <tr><td>20</td><td>IP network interface</td></tr> <tr><td>21</td><td>misc configuration on switch card</td></tr> <tr><td>22</td><td>ONU base manage configuration</td></tr> <tr><td>23</td><td>ONU advanced manage configuration</td></tr> <tr><td>24</td><td>ONU UNI port configuration</td></tr> <tr><td>25</td><td>ONU Queue configuration</td></tr> <tr><td>26</td><td>ONU ACL Rules configuration</td></tr> <tr><td>27</td><td>ONU port VLAN configuration</td></tr> <tr><td>28</td><td>ONU authentication</td></tr> <tr><td>29</td><td>ONU port QoS configuration</td></tr> <tr><td>30</td><td>ONU IGMP Snooping configuration</td></tr> <tr><td>31</td><td>ONU loopback test configuration</td></tr> <tr><td>32</td><td>ONU dynamic mac table configuration</td></tr> <tr><td>33</td><td>Extern network management module</td></tr> <tr><td>34</td><td>OLT basic configuration</td></tr> <tr><td>35</td><td>OLT advanced configuration</td></tr> </tbody> </table>	moduleid	module name	3	common mbuf pool	4	HDLC driver	5	inter-board communicaiton protocol	9	device online status maintenance	10	system basic configuration	11	user manager	12	switch port attribute management	13	switch port status poll task	14	switch port statistics poll task	15	trunk module	16	mirroring module	17	normal vlan module	18	protocol type based VLAN	19	rapid spanning tree module	20	IP network interface	21	misc configuration on switch card	22	ONU base manage configuration	23	ONU advanced manage configuration	24	ONU UNI port configuration	25	ONU Queue configuration	26	ONU ACL Rules configuration	27	ONU port VLAN configuration	28	ONU authentication	29	ONU port QoS configuration	30	ONU IGMP Snooping configuration	31	ONU loopback test configuration	32	ONU dynamic mac table configuration	33	Extern network management module	34	OLT basic configuration	35	OLT advanced configuration
moduleid	module name																																																														
3	common mbuf pool																																																														
4	HDLC driver																																																														
5	inter-board communicaiton protocol																																																														
9	device online status maintenance																																																														
10	system basic configuration																																																														
11	user manager																																																														
12	switch port attribute management																																																														
13	switch port status poll task																																																														
14	switch port statistics poll task																																																														
15	trunk module																																																														
16	mirroring module																																																														
17	normal vlan module																																																														
18	protocol type based VLAN																																																														
19	rapid spanning tree module																																																														
20	IP network interface																																																														
21	misc configuration on switch card																																																														
22	ONU base manage configuration																																																														
23	ONU advanced manage configuration																																																														
24	ONU UNI port configuration																																																														
25	ONU Queue configuration																																																														
26	ONU ACL Rules configuration																																																														
27	ONU port VLAN configuration																																																														
28	ONU authentication																																																														
29	ONU port QoS configuration																																																														
30	ONU IGMP Snooping configuration																																																														
31	ONU loopback test configuration																																																														
32	ONU dynamic mac table configuration																																																														
33	Extern network management module																																																														
34	OLT basic configuration																																																														
35	OLT advanced configuration																																																														

	36	OLT bridge configuration
	37	OLT DBA configuration
	38	OLT aggregate bandwidth configuration
	39	OLT acl rules configuration
	40	OLT priority copy mapping configuration
	41	OLT IGMP configuration
	42	OLT PPPOE configuration
	43	Logical Link basic configuration
	44	Logical Link advanced configuration
	45	Logical Link SLA configuration
	46	Logical Link VLAN configuration
	47	Logical Link blocked link configuration
	48	Logical Link dynamic and static MAC
	50	on-line upgrade module
	51	port statistics alarm and threshold

4. System Root Directory

Ater you log in successfully , input “? ”or “help”to show the current directory

epon> ?

[no] copy-log	- print log messages on the current shell.
debug	- enter debug mode
enable	- enter privileged mode
exe	- Execute raw commands(global C functions).
show	- show various parameters

4.1. Enable System Log Printed to Super Terminal

Command Grammar	[epon>] [no] copy-log
Function	Show current System Log

4.2. System Debug Mode

Command Grammar	epon>> debug
Function	enter debug mode ,

【Remark】

entering“exit”could return to the current mode .

You will find the command as follows after entering debug mode :

epon% ?	input “? ”or “help”to show the current directory
debug	- debug specific module
dump	- show module internal data
log-lvl	- set log level for specific module

4.2.1.debug

Command Grammar	epon% debug module <moduleid>
Function	Configure the module’s debug functions

【Remark】

This command isn’t valid yet .

4.2.2.dump

Command Grammar	epon% dump module <moduleid>
Function	Configure the module’s dump functions
<moduleid>	Module ID ,format please refer to 3.3 typical Parameter category

4.2.3.log-lvl

Command Grammar	epon% Log-lvl module <moduleId> <level>
Function	Change module's LOG level
<moduleId>	Module ID , definition format refer to typical Parameter category illustration .
<level>	There are 5 level for LOG level, marked from 0 to 4 .0 is the highest level. 0:critical event 1:important event 2:general event 3:trivial event 4:debug message

4.3. Enable Mode

Command Grammar	epon> enable
Function	Enter "enable management mode and provides enable password.

【Example】

1. enter enable management mode:

```
epon>enable
password:
epon#
```

The default password to enter enable mode is admin.

epon# ? Input“? ” or “help”to show the follwing directory:

- igmp-snooping** - configure global IGMP Snooping
- mac-address** - ctrl-card dynamic mac address table management
- mirror** - mirroring configuration
- network** - configure network parameters
- olt** - enter olt config mode
- passwd** - change enable password
- rstp** - enter rapid spanning tree config mode
- show** - display configuration

swmode	- set basic switch mode
swport	- enter switch port config mode
system	- configure system basic parameters
trunk	- enter trunk config mode
user	- User configuration
vlan	- enter vlan config mode

4.3.1. Switch Control Module MAC Address Management

4.3.1.1. Configure switch control module's MAC Aging Time

Command Grammar	epon# mac-address aging <timeout>
Function	Configure switch control module's MAC address aging time
<timeout>	MAC aging time ,with value range from 0 to 255.step length is 15 seconds.

4.3.1.2. Show switch control module's MAC Address List

Command Grammar	epon# mac-address show
Function	Show switch control module's MAC address list.

4.3.2. Port mirror Management

4.3.2.1. Mirror Destination Port

Command Grammar	epon# mirror destination port <port >
Function	Configure the designated port for the switch control module as the mirror destination port
<port >	Designate a port as the mirror destination port with value range from gel to ge4.

4.3.2.2. Add Mirror Source Port

Command Grammar	epon# mirror source add port < portlist > < direction >
Function	Configure added mirror source port ,available for designating some port's uplink ,downlink or bidirectional data flow as mirror source .
< port list >	Designate some port as mirror source port .Designation means could refer to 3.3 Typical Parameter category Illustration.
< direction >	Designate mirror source's data flow direction with vale as follows: ingress egress both

4.3.2.3. Delete Mirror Source Port

Command Grammar	epon# mirror source delete port < portlist > < direction >
Function	Delete mirror source port ,which could appoint one direction's data flow as mirror source .
< port list >	Port list
< direction >	Appoint deleted mirror sour's data flow direction: ingress egress both

4.3.2.4. Clear Mirror Source

Command Grammar	epon# mirror source clear
------------------------	----------------------------------

Function	Clear all mirror source including all source port and source VLAN.
-----------------	--

4.3.3. Network Configuration Mode

Command Grammar	epon# network
Function	Configure inband and outband management port's IP address.

【Example】

1. Enter network management mode

epon#network
epon(net)#

epon(net)# input “?” or “help” to show the following directory

[no] address - set network interface address

[no] gateway - configure network default gateway

4.3.3.1. Configure Management Port's IP and Sub Mask

Command Grammar	epon(net)# address <i><ifx-name></i> <i><ip-addr></i> <i><ip-mask></i>
Function	Configure network port's IP address and submask. Currently our network management port includes inband network management port vi0 and outband network management port cpm0. input address <i><ifx-name></i> could show the current networking configuration.
< ifx-name >	Appointed ip port name ,which could be vi0 or cpm0 ,port format expression mode refer to typical Parameter category.
<ip-addr>	Configure IP address
< ip-mask >	Configure appointed IP address's network mask.

【Example】

1.Enquiry the current inband network management port's network configuration:

```
epon(net)#address vi0
Interface vi0:
    Ip address      :192.168.1.100
    Netmask         :255.255.255.0
    associated vlan :1
    admin status    :operational
```

Example 2:Configure inband management IP as 192.168.1.1 ,mask is 255.155.155.0

```
epon(net)#address vi0 192.168.1.1 255.255.255.0
```

Example 3:Configure outband management IP as 192.168.1.2 and mask is 255.255.255.0

```
epon(net)#address cpm0 192.168.1.2 255.255.255.0
```

4.3.3.2. Configure NMS Port Gateway

Command Grammar	epon(net)# gateway <ip-addr>
Function	Configure NMS port's gateway. Input command gateway to show the current gateway information.
<ip-addr>	Configure the appointed gateway address.

4.3.4.OLT Management Mode

4.3.4.1. Enter OLT Management Mode

Command Grammar	epon# olt <slotid> <oltid>
Function	Enter OLT management mode to configure OLT,downlink and ONU . just input "olt" could show the current online OLT .
<slotid>	olt pon module slot with value 0 .
<oltid>	Pon ID with valid value 1 and 2 .

【Example】

1.Show current online OLT :

epon#olt			
Following is online olt list:			
Slot	Olt	Mac Address	Online Status
0	1	00:a1:02:01:03:40	Online
0	2	00:a1:02:01:03:40	Online

2. Manage PON-1 .

epon#olt 0 1
epon(slot0-olt1)#

epon(slot0-olt1)# ?	input“? ”or “help” to show the command directory :
admin	- set olt administrate status
bridge	- set olt bridge configuration
default	- reset olt default configuration
ext-mgmt	- extern network management
factory	- Restore factory settings,onuid will be redistributed.
link	- enter link config mode
onu	- enter onu config mode
overwrite-linkid	- overwrite linkid when linkid is exhausted
overwrite-onuid	- overwrite onuid when onuid is exhausted
p2p	- onu p2p management
restore	- restore to saved configuration
save	- save pon card configuration
show	- show olt base configuration

4.3.4.2. Enable OLT

Command Grammar	epon(slot0-olt1)# admin <enable disable>
Function	Enable/disable OLT
<enable>	Enable OLT
<disable>	Disable OLT

4.3.4.3. OLT Bridge Configuration

Command	epon(slot0-olt1)# bridge
----------------	---------------------------------

Grammar	
Function	Show current bridge setting

【example】

1. Show OLT's current bridge setting

epon(slot0-olt1)#bridge	
Bridge Configuration:	
learned mac age limit	:0 (ms)
bridge vlan number	:64 (bridges)
allow simple bridge	:YES
mac learn overwrite	:NO
discard unknown mac	:NO
allow tagged frame	:YES

4.3.4.3.1. MAC Address Aging Time

Command Grammar	epon(slot0-olt1)# bridge limit <limit>
Function	Change MAC address's aging time .0 means not to learn MAC , the unit is 1ms .
<limit>	Parameter range 0-2419200

4.3.4.3.2. Bridge VLAN Number Configuration

Command Grammar	epon(slot0-olt1)# bridge vlan-num <vlanNum>
Function	Set bridge vlan number(tk3723 chipset OLT 's fixed number is 64)
<vlanNum>	Fix number is 64

4.3.4.3.3. MAC Address Overwrite Configuration

Command	epon(slot0-olt1)# bridge overwrite <enable disable>
----------------	--

Grammar	
Function	Set overwrite MAC address mode
<enable / disable>	Parameters <enable disable> with the meaning as follows: enable:When MAC address is full ,new MAC overwrite existing MAC address . disable:When MAC address is full ,ignore the new MAC address .

4.3.4.3.4. Unknown MAC Restriction Configuration

Command Grammar	epon(slot0-olt1)# bridge dsc-unk-mac <enable / disable>
Function	Set unknown MAC restriction mode
<enable / disable>	enable:unknown DA downlink packet deliver the broadcast to all ports . disable:unknown DA downlink packet is abandon

4.3.4.3.5. Forward Tag Frame Configuration

Command Grammar	epon(slot0-olt1)# bridge tag-on-sbrg <enable / disable>
Function	Set tag forwarding rules under simple bridge mode.
<enable / disable>	enable:allow forwarding tag frame disable:dump tag frame

4.3.4.4. Restore PON Default Setting

Command Grammar	epon(slot0-olt1)# default
Function	Restore PON Default Setting

【Remark】

The command will delete PON module's all setting and restore the ex-factory default setting .And the PON module will reboot automatically.

4.3.4.5. Link Management Mode

Command Grammar	epon(slot0-olt1)#link <linkid>
Function	Enter LINK management mode and configure link Parameter. ,
<linkid>	Designated linked with value range from 1 to 256 .

【Example】

1.Show the current LINK :

```
epon(slot0-olt1)#link
Following is link list:
  Link Id  Mac Address           Online Status
  1        00:a1:02:01:07:30    Online
  2        00:a1:02:01:07:31    Offline
  3        00:a1:02:03:bc:f8    Offline
  4        00:a1:02:01:97:d0    Offline
  5        e0:67:b3:03:be:e8    Offline
  6        00:a1:02:04:e7:08    Offline
  7        00:a1:02:01:07:38    Online
  8        00:a1:02:01:07:39    Online
```

2.Enter Link1 management interface :

```
epon(slot0-olt1)#link 1
epon(slot0-olt1-link1)#
```

epon(slot0-olt1-link1)# ? input“?”or “help”to show command directory:

```
[no] block          - block link
bridge-mode         - only support simple-bridge mode now.
dynamic-mac-clear   - clear dynamic mac table
dynamic-mac-list    - display all dynamic mac table
dynamic-mac-refresh - refresh dynamic mac table
rediscover          - force link rediscovery
show                - show link basic configuration
sla                 - set link SLA parameters
static-mac-add      - add a static mac
static-mac-del      - delete a static mac
static-mac-list     - display all static mac table
```

4.3.4.5.1. Block Current Link

Command Grammar	epon(slot0-olt1-link1)# block
Function	Block current link to stop the link's data flow.

4.3.4.5.2. Remove the Current Link Block

Command Grammar	epon(slot0-olt1-link1)# no block
Function	Remove the current link block to restore the link's data flow.

4.3.4.5.3. Clear Link's Dynamic MAC Address List

Command Grammar	epon(slot0-olt1-link1)# dynamic-mac-clear
Function	Clear link's dynamic MAC address list

4.3.4.5.4. Show Link's Dynamic MAC Address List

Command Grammar	epon(slot0-olt1-link1)# dynamic-mac-list
Function	Show all the MAC address list learned from the link

【Remark】

Please use the command “dynamic-mac-refresh” to refresh the link's dynamic MAC address before showing the link's dynamic MAC address .

4.3.4.5.5. Refresh Link's Dynamic MAC Address List

Command Grammar	epon(slot0-olt1-link1)# dynamic-mac-refresh
Function	Refresh link's dynamic MAC Address

4.3.4.5.6. Force Rediscovering Link

Command Grammar	epon(slot0-olt1-link1)# rediscover
Function	Force the link rediscovering to OLT

4.3.4.5.7. Show LINK Basic Information

Command Grammar	epon(slot0-olt1-link1)# show
Function	Show the link's current basic configuration information

【Example】

1.Show the current link's basic configuration information :

```
epon(slot0-olt1-link1)#show
Link Basic Configurations:
  associated onu id          :1
  assigned link id by olt   :0
  mac address                :00:a1:02:0a:a1:08
  online status              :Online
  key exchange timer        :0 (sec)
  bridging type              :simple-bridge
  mac table entry limit     :64 (entries)
  cross connected link id   :NO
```

4.3.4.5.8. Link SLA Configuration

4.3.4.5.8.1. Configure Link's Minimum Guaranteed Bandwidth

Command Grammar	epon(slot0-olt1-link1)#sla <dir> min-bw <min-bw>
Function	Configure the link's uplink or downlink's minimum guaranteed bandwidth
<dir>	Appoint the link sla's direction : downstream upstream
<min-bw>	Appoint the link 's minimum guaranteed bandwidth with valid value from 0,256 to 1000000. 0 means disabling the minimum guaranteed bandwidth function.

【Remark】

The minimum bandwidth much be lower than or equal to the maximum allowed bandwidth .

4.3.4.5.8.2. Configure Link's Maximum Allowed Bandwidth

Command Grammar	epon(slot0-olt1-link1)#sla <dir> max-bw <max-bw>
Function	Configure the link's uplink or downlink maximum allowed bandwidth .
<dir>	Appoint the link SLA's configuration direction : downstream upstream
<max-bw>	Appoint the link 's maximum allowed bandwidth with valid value from 256 to 1000000. 0 means disabling the minimum guaranteed bandwidth function.

【Remark】

The maximum bandwidth must higher than or equal to the minimum guaranteed bandwidth .

4.3.4.5.8.3. Configure Link Transmission Time Delayed Level

Command Grammar	epon(slot0-olt1-link1)#sla <dir> level <level>
Function	Configure uplink or downlink's transmission delayed time level.
<dir>	Two direction Parameter optional : downstream upstream
<level>	Appoint downlink or uplink's transmission delayed time level with the valid value as follows : Sensitive : sensitive service could be given the priority to transmit . tolerant : non-sensitive service

4.3.4.5.8.4. Configure Link's Maximum Burst Flow

Command Grammar	epon(slot0-olt1-link1)#sla <dir> burst-size <burst>
Function	Configure uplink or downlink's maximum burst flow .
<dir>	Two configuration direction as follows : downstream upstream
<burst>	Appoint the link 's maximum burst flow with the valid value range from 1 to 256.

4.3.4.5.8.5. Show LINK SLA Configuration

Command Grammar	epon(slot0-olt1-link1)#sla <dir>
Function	Show uplink or downlink's SLA configuration information
<dir>	downstream or upstream

【Example】

1. Show current uplink's SLA configuration information :

```
epon(slot0-olt1-link1)#sla upstream
Current Link SLA configuration(Upstream):
```

minimum guaranteed bandwidth	:0	(Kbps)
maximum allowed bandwidth	:1000000	(Kbps)
delay sensitive	:Tolerant	
max burst size	:100	(KBytes)
sla state	:Enable	

2. Show downlink's SLA configuration information :

epon(slot0-olt1-link1)#sla downstream		
Current Link SLA configuration(Downstream):		
minimum guaranteed bandwidth	:0	(Kbps)
maximum allowed bandwidth	:1000000	(Kbps)
delay sensitive	:Tolerant	
max burst size	:100	(KBytes)
sla state	:Enable	

4.3.4.5.9. Add Link's Static MAC Address

Command Grammar	epon(slot0-olt1-link1)# static-mac-add <mac>
Function	Add link's static MAC address
<mac>	Input MAC address

4.3.4.5.10. Delete Link's Static MAC Address

Command Grammar	epon(slot0-olt1-link1)# static-mac-del <mac>
Function	Delete Appointed Link's Static MAC Address
<mac>	Input the deleted MAC address

4.3.4.5.11. Show Link's Static MAC Address List

Command Grammar	epon(slot0-olt1-link1)# static-mac-list
------------------------	--

Function	Show the link's static MAC address
-----------------	------------------------------------

4.3.4.6. ONU Management Mode

Command Grammar	epon(slot0-olt1)#onu <onuid>
Function	Enter ONU management mode and configure the ONU Parameter.
<onuid>	Input onuid with the valid value range from 1 to 64

【Example】

1.Show current online ONU

```
epon(slot0-olt1)#onu
Following is online onu list:
```

slotId	oltId	onuid	deviceType	basedMac	hWRev	fwRev
0	1	1	ONU4D	00:a1:02:01:07:30	V03	Vc2.30
0	1	6	ONU2D-G	00:a1:02:01:07:38	V02	Vc2.42

2. Enter ONU1 management interface

```
epon(slot0-olt1)#onu 1
epon(slot0-olt1-onu1)#
```

```
epon(slot0-olt1-onu1)# ?      input "?" or "help" to show command directory
catv                          - catv switch configuration
ctc                            - CTC operations
default                        - restore to default setting
iadParamCfg                   - iadParamCfg
info                           - onu device user information
loopback-test                 - loopback test
mac-address                   - onu addresses management
port                           - enter onu port config mode
port-protect                   - isolate onu ports
reboot                         - reboot the system
restore                        - restore to saved configuration
rstp                           - onu rapid spanning tree config
save                           - save onu configuration
user-traffic                   - enable or disable user traffic
vlan-type                      - set onu additional vlan ethertype
```

4.3.4.6.1. Restore ONU Default Configuration

Command Grammar	pon(slot0-olt1-onu1)# default
Function	Restore ONU default configuration

【Remark】

The command will delete all ONU's configuration to restore default configuration .The ONU will reboot automatically .

4.3.4.6.2. IGMP Snooping Configuration

4.3.4.6.2.1. ONU IGMP Global Parameter Configuration

4.3.4.6.2.1.1. Fast leave enable

Command Grammar	epon(slot0-olt1-onu1)# ctc igmp-snooping fast-leave <state>
Function	Enable /disable fast leave function
<state>	enable disable.

4.3.4.6.2.1.2. Multicast Switching Mode

Command Grammar	epon(slot0-olt1-onu1)# ctc igmp-snooping mode <mode>
Function	Add a IGMP address and a port number
<mode>	igmp-mld-snooping controllable-igmp-mld igmp-snooping-only controllable-igmp disable *Only igmp-mld-snooping and disable are valid

4.3.4.6.2.2. IGMP Port Configuration

4.3.4.6.2.2.1. Set number of igmp groups for onu port

Command Grammar	epon(slot0-olt1-onu1-fe1)# ctc igmp-snooping max-group <groups>
Function	set number of igmp groups for onu port
<groups>	number of igmp groups,<0~64>

4.3.4.6.2.2.2. Set multicast strip mode

Command Grammar	epon(slot0-olt1-onu1-fe1)# ctc igmp-snooping tag-handle <mode>
Function	Set multicast strip mode
<mode>	not-strip-vlan-tag - Not Strip Vlan Tag strip-vlan-tag - Strip Vlan Tag switch - Switch VLAN tag

4.3.4.6.2.2.3. add igmp-vlan-group list on ONU user port

Command Grammar	epon(slot0-olt1-onu1-fe1)# ctc igmp-snooping vlan-tag-list <vlanTagList>
Function	add igmp-vlan-group list at ONU user port
<vlanTagList>	- vlan tag list,<Combination of 1~4094, or null>

4.3.4.6.2.2.4. Show multicast setting on ONU user port

Command Grammar	epon(slot0-olt1-onu1-fe1)# ctc igmp-snooping show
Function	Show multicast setting on ONU user port

4.3.4.6.3. Configure ONU User Information

Command Grammar	epon(slot0-olt1-onu1)# info <info>
Function	Configure ONU user information; Just input "info" to show the current ONU user's information .

<info>	User information bytes with longest bytes 64
---------------------	--

4.3.4.6.4. ONU Link Loopback Test

Command Grammar	epon(slot0-olt1-onu1)# loopback-test
Function	Test ONU link status and this command is interactive command which need the user to provide the following Parameterstep by step . loopback location: mac 或 phy number of frames:1-65535 payload length:64-1500 vlan tag:0-4094

【Example】

1.Test ONU Link

<pre>epon(slot0-olt1-onu1)#loopback-test please offer the loopback test parameter: loopback location[mac phy]:mac number of frames[1~65535]:100 payload length[64~1500]:64 vlan tag[0~4094]:0 testing... result: frames sent :100 frames received :100 corrupted frames receive :0 minimum Delay (us) :2512 maximum Delay (us) :5788 mverage Delay (us) :4135</pre>	
---	--

4.3.4.6.5. Show ONU Dynamic MAC Address List

Command Grammar	epon(slot0-olt1-onu1)# mac-address-show
Function	Show ONU's dynamic learning MAC address gloably.

4.3.4.6.6. ONU Port Management Mode

Command Grammar	epon(slot0-olt1-onu1)# port < uni-port >
Function	Enter ONU port management mode and configure the ONU port's Parameter.
< uni-port >	Appoint onu port number with valid value range from fe1 to fe24.

【Example】

1.Enter ONU1's port 1 interface

```
epon(slot0-olt1-onu1)#port fe1
epon(slot0-olt1-onu1-fe1)#
```

```
epon(slot0-olt1-onu1-fe1)# ?      input "?" or "help" to show the command directory
attribute          - onu port attribute config
bridge             - onu port bridge parameter config
ctc                - CTC mgmt mode
dynamic-mac-clear - clear dynamic mac table
dynamic-mac-list  - display all dynamic mac table
[no] enable        - enable onu port
info               - set onu port user information
qos                - onu port qos config
```

4.3.4.6.6.1. Configure ONU port's Parameter Attribute

4.3.4.6.6.1.1. Show ONU Port Parameter

Command Grammar	epon(slot0-olt1-onu1-fe1)# attribute
Function	Show ONU port's Parameter attribute.

【Example】

1:Show ONU1 's port 1 attribute

```
epon(slot0-olt1-onu1-fe1)#attribute
ONU(0/1/1) Port fe1 attribute:
  auto negotiation :enable
  flow control     :disable
  speed            :10m
```

duplex	:half
--------	-------

4.3.4.6.6.1.2. Configure ONU Port Auto-Negotiation

Command Grammar	epon(slot0-olt1-onu1-fe1)# attribute auto-nego <oper>
Function	Configure ONU port to be auto-negotiable
<oper>	Value input is <enable or disable>: enable : enable the port's auto-negotiation function disable : Disable the port's auto-negotiation function

4.3.4.6.6.1.3. Configure ONU Port Speed

Command Grammar	epon(slot0-olt1-onu1-fe1)# attribute speed <speed>
Function	Configure ONU port's speed
<speed>	ONU port speed with valid value as follows:10m , 100m , 1000m

4.3.4.6.6.1.4. Configure ONU Port's Duplex Function

Command Grammar	epon(slot0-olt1-onu1-fe1)# attribute duplex < duplex>
Function	Configure ONU port's duplex status
< duplex>	ONU port's duplex status with value "half" or full

4.3.4.6.6.1.5. Configure ONU Port Flow Control Function

Command Grammar	epon(slot0-olt1-onu1-fe1)# attribute flow-ctrl <oper>
Function	Configure ONU port's flow control function
< oper>	Enable/disable ONU port flow control function Enable: enable ONU port flow control function Disable:disable ONU port flow control function

4.3.4.6.6.2. Configure ONU port's Bridge Parameter

4.3.4.6.6.2.1. Show ONU Port Bridge Parameter

Command Grammar	pon(slot0-olt1-onu1-fe1)# bridge
Function	Show ONU port bridge Parameter

【example】

1:Show ONU port-1's bridge Parameter

<pre>epon(slot0-olt1-onu1-fe1)#bridge ONU(0/1/1) Port fe1 bridge parameter: automatic learning entry limit :16 learned entry age limit :0s forwarding mode :802.1d mode</pre>	
--	--

4.3.4.6.6.2.2. Configure ONU Port's Dynamic MAC Limits

Command Grammar	epon(slot0-olt1-onu1-fe1)# bridge <entry-limit>
Function	Configure ONU port's dynamic learning MAC number
<entry-limit>	Maximum learning MAC number with valid value from 0 to 64;0 means not to learn MAC address

4.3.4.6.6.2.3. Configure ONU Port's MAC Aging Time

Command Grammar	epon(slot0-olt1-onu1-fe1)# bridge age-time <age-time>
Function	Configure ONU port's Aging time of MAC address
<age-time >	MAC address aging time with valid value from 0 to 32768; 0 means not to age MAC address

4.3.4.6.6.2.4. Configure ONU Port's Forward Mode

Command Grammar	epon(slot0-olt1-onu1-fe1)# bridge forward-mode <forward-mode>
------------------------	--

Function	Configure ONU port's forward mode
<forward-mode>	Forward mode with valid value such as 8021d,drop-until-learned; 8021d mode :unknown MAC packet broadcast to all ports ; Drop-until-learned mode: drop unknown MAC packet

4.3.4.6.6.3. Clear ONU Port's Dynamic MAC List

Command Grammar	epon(slot0-olt1-onu1-fe1)# dynamic-mac-clear
Function	Clear ONU port's dynamic MAC list

4.3.4.6.6.4. Show ONU Port's Dynamic MAC List

Command Grammar	epon(slot0-olt1-onu1-fe1)# dynamic-mac-list
Function	Show ONU port's dynamic MAC List

4.3.4.6.6.5. Enable ONU UNI Port

Command Grammar	epon(slot0-olt1-onu1-fe1)# enable
Function	Enable ONU port to make sure normal communication

4.3.4.6.6.6. Disable ONU UNI Port

Command Grammar	epon(slot0-olt1-onu1-fe1)# no enable
Function	Disable ONU port to stop the data flow communication

4.3.4.6.6.7. Configure ONU Port's User Information

Command Grammar	epon(slot0-olt1-onu1-fe1)# info <info>
Function	Set ONU port's user information; Input "info" to show ONU port's user information

<info>	User information bytes length ,with the longest length 64 bytes
---------------------	---

4.3.4.6.6.8. Configure ONU Port's Uplink Speed Limit

Command Grammar	epon(slot0-olt1-onu1-fe1)# qos ingress-policing < max-rate> < traffic-type>
Function	Set ONU port's uplink bandwidth limits. Input "qos ingress-policing" to show the current uplink speed limit configuration information .
< max-rate>	Maximum uplink bandwidth ;unit :kbps ;valid value:0-100000;
< traffic-type>	Appoint speed limit's packet type with value as follows: Broadcast; broadcastAndMulticast; broadcastMulticastAndFloodedUnicast; all

4.3.4.6.6.9. Configure ONU Port's Downlink Speed Limit

Command Grammar	epon(slot0-olt1-onu1-fe1)# qos egress-shapping < max-rate> <schedule-algorithm>
Function	Set ONU port's downlink bandwidth limits. Input "qos egress-shapping" to show the current downlink speed limit configuration information .
< max-rate>	Maximum downlink bandwidth ;unit :kbps ;valid value:0-100000;
<schedule-algorithm>	Port's output flow shaping 's adjusty calculation method with valid value :: weighted-fair strict-priority

4.3.4.6.7. ONU UNI Port VLAN Configuration

4.3.4.6.7.1.1. Add VLAN

Command Grammar	epon(slot0-olt1-onu1-fe1)# ctc vlan add cEtherType <ctype> cVLANTag <cvlantag> sEtherType <stype> sVLANTag <svlantag>
Function	Add appointed ONU UNI port's VLAN.

< ctype >	Ethernet type, ranging from 0 to 65536, typically set to 33024 (0x8100)
< cvlantag >	valid value range from 0 to 4095
< stype >	Converted vlan Ethernet type, ranging from 0 to 65536. UNI port is set to tag or trunk mode, this parameter should be set to 0 or null.
< svlantag >	Conversion vlan tag in the range of 0 to 4095. UNI port is set to tag or trunk mode, this parameter should be set to 0 or null.

【Example】

1. Add vlan100 to ONU UNI port 1:

```
epon(slot0-olt1-onu1-fe1)#ctc vlan add cEtherType 33024 cVLANTag 100
```

2. Translate vlan100 to vlan200 at ONU UNI port 1:

```
epon(slot0-olt1-onu1-fe1)#ctc vlan add cEtherType 33024 cVLANTag 100 sEtherType 33024 sVLANTag 200
```

4.3.4.6.7.1.2. Delete VLAN

Command Grammar	epon(slot0-olt1-onu1-fe1)#ctc vlan delete cVLANTag <cvlantag>
Function	Delete appointed ONU UNI port's Vlan
< vlanid >	Appointed vlan to be deleted with valid value range from 0 to 4094

4.3.4.6.7.1.3. Configure ONU UNI Port's VLAN Forwarding Mode and PVID

Command Grammar	epon(slot0-olt1-onu6-fe1)#ctc vlan policy <policy> etherType <type> pvid <pvid>
Function	Configure ONU UNI port's VLAN forwarding Mode and PVID
< policy >	The values are as follows <policy> policy0 Transparent mode, ignoring etherType and pvid value policy1 Access mode policy2 VLAN translation mode policy4 VLAN trunk mode.
< type >	Ethernet type, ranging from 0 to 65536, typically set to 33024 (0x8100)
< pvid >	valid value range from 0 to 4095

【Example】**1.Set ONU1 port 1 transparent mode:**

```
epon(slot0-olt1-ONU1-fe1)#ctc vlan policy policy0
```

2 Set ONU1 port 1 to tag mode, set the port pvid to 100:

```
epon(slot0-olt1-ONU1-fe1)#ctc vlan policy policy1 etherType 33024 pvid 100
```

3 Set ONU1 port 1 to trunk mode, set the port pvid to 1:

```
epon(slot0-olt1-ONU1-fe1)#ctc vlan policy policy4 etherType 33024 pvid 1
```

【Illustration】

1. Policy0: transparent mode,.

Direction	Frame Type	Approach
Ingress	Untagged	without any changes (to retain the original VLAN TAG), forwarding
	Tagged	without any changes, forwarding
Egress	Untagged	without any changes (to retain the original VLAN TAG), forwarding
	Tagged	without any changes, forwarding

2. policy1 : Access mode

Direction	Frame Type	Approach
Ingress	Untagged	Insert VLAN tag (main parameter is the VID), forwarding. (TPID = 0x8100, Pri = 0, VID = Port VID)
	Tagged	ignore the frame
Egress	Untagged	ignore the frame
	Tagged	Forward to the appropriate UNI port and strip VLAN TAG according to VID; if frame tagged VLAN ID is not equal to Port VID, the frame will be discarded.

3. policy2 : Translation mode

Direction	Frame Type	Approach
Ingress	Untagged	Insert VLAN Tag, forwarding. (TPID = 0x8100, Pri = 0,VID = Port VID)
	Tagged	If VID of frame is included in input VLAN list of the UNI port the VID will be translated to output VID. Then forward the frame. Discard the frame if VID of frame is not included in input VLAN list of the UNI port
Egress	Untagged	ignore the frame
	Tagged	If VID of frame is included in output list of the UNI port the VID will be translated to input VID. Then forward the frame. Strip VLAN tag and forward the frame if the VID is equal

		to PVID Discard the frame if VID of frame is not included in the output VLAN list of the UNI port.
--	--	---

4. policy4 : Trunk mode

Direction	Frame Type	Approach
Ingress	Untagged	Insert VLAN Tag, forwarding. (TPID = 0x8100, Pri = 0,VID=Port VID)
	Tagged	Forward the frame if VID of frame is included in “allows VLAN” list; Discarded the frame if VID of frame isn’t included in “allows VLAN” list;
Egress	Untagged	ignore the frame
	Tagged	Forward the frame if VID of frame is included in “allows VLAN” list; Strip VLAN TAG and forward the frame if the VID is equal to PVID Discarded the frame if VID of frame isn’t included in “allows VLAN” list;

4.3.4.6.7.1.4. Show ONU UNI Port’s VLAN Configuration

Command Grammar	epon(slot0-olt1-onu1-fe1)# ctc vlan show
Function	Show ONU UNI port’s VLAN configuration information

4.3.4.6.8. Reboot ONU

Command Grammar	epon(slot0-olt1-onu1)# reboot
Function	Reboot onu

4.3.4.6.9. Configure RSTP Function

Command Grammar	epon(slot0-olt1-onu1)# rstp <oper>
-----------------	--

Function	Configure ONU's rapid spanning tree protocol (RSTP) function; Input "rstp" to show current RSTP status
<oper>	Enable/disable ONU RSTP function with valid value as follows: Enable: enable ONU RSTP function Disable: disable ONU RSTP function

4.3.4.6.10. Save ONU configuration

Command Grammar	pon(slot0-olt1-onu1)# save
Function	Save ONU's all configuration .

4.3.4.6.11. Configure ONU's Traffic Flow Management

Command Grammar	epon(slot0-olt1-onu1)# user-traffic <oper>
Function	Configure ONU user's traffic flow management When input "user" to show the onu user's current traffic flow
<oper>	enable :enable onu user's traffic flow Disable: disable onu user's traffic flow

4.3.4.6.12. Configure ONU VLAN's Ethernet Parameter

Command Grammar	epon(slot0-olt1-onu1)# vlan-type ethtype <type> upstream <uptag> downstream <dntag>
Function	Configure onu vlan's Ethernet type and set this vlan's Ethernet traffic direction; Input "vlan-type" to show onu's current VLAN Ethernet information.
<type>	VLAN's Ethernet type with default value as 0x8100 and the valid value range from 0 to 65535
<uptag>	Whether add the vlan tag of the vlan Ethernet type for the uplink traffic ;

	tag : add tag Untag: do not add tag
<dntag>	Whether add the vlan tag of the vlan Ethernet type for the downlink traffic ; tag : add tag Untag: do not add tag

4.3.4.7. Configure Link ID Overwrite Function

Command Grammar	epon(slot0-olt1)# overwrite-linkid <oper>
Function	Whether new authorized link overwrites the existing link ID after the Link ID is set .
<oper>	Enable: new Link overwrites existing Link ID. Disable: new Link does not overwrite existing Link ID.

4.3.4.8. Configure ONU ID Overwrite Function

Command Grammar	epon(slot0-olt1)# overwrite-onuid < oper >
Function	Whether new authorized ONU overwrites the existing ONU ID after the ONU ID is set .
<oper>	Enable: new ONU overwrites existing ONU ID. Disable: new ONU doesn't overwrites existing ONU ID .

4.3.4.9. Reboot PON Card

Command Grammar	epon(slot0-olt1)# reboot
Function	Reboot PON card

4.3.4.10. Save PON card configuration

Command Grammar	epon(slot0-olt1)# save
Function	Save PON card's all configuration

4.3.4.11. Show OLT's Basic Information

Command Grammar	epon(slot0-olt1)# show
Function	Show OLT's basic configuration

【Example】

1. Show OLT's current basic configuration

epon(slot0-olt1)#show	
Olt Basic Configurations:	
mac address	:00:0d:b6:37:23:00
work state	:Online
enable status	:Enable
max permitted link number	:210
registered link number	:1
accessed onu number	:1
link id exhausted	:NO
onu id exhausted	:NO
link id overwrite	:NO
onu id overwrite	:NO

4.3.5. Configure Enable Password Management

Command Grammar	epon# passwd
Function	Enter the enable password changing mode .

【Example】

1.Change enable password :

```
epon#passwd
Enter new enable password:
Confirm new enable password:
epon#
```

【Remark】

Please do save the configuration under the system directory after changing the password and reboot the system to make the setting valid .

4.3.6.RSTP Configuration Mode

Command Grammar	epon# rstp
Function	Enter switch control module's RSTP management mode 进

【Example】

1.Enerer RSTP Management Mode

```
epon#rstp
epon(rstp)#
```

```
epon(rstp)# ?      input "? " or "help" to show current directory
  bridge            - bridge
  disable           - disable rstp
  enable            - enable rstp
  hold-count        - set rstp transmit hold count
  port              - rstp port parameter configuration
  show              - show rstp configuration
```

4.3.6.1. Configure RSTP Bridge Parameter

4.3.6.1.1. Bridge Forward Delay

Command	epon(rstp)# bridge fdelay < fdelay >
----------------	---

Grammar	
Function	Set RST Bridge delayed forward
< fdelay >	Value range : 4-30 ;must demand the following bind relation: $2 \times (\text{ForwardDelay} - 1.0\text{second}) \geq \text{MaxAge}$ MaxAge is bridge infomration's maximum valid time ; ForwardDelay: forward delay

4.3.6.1.2. Bridge Maximum Valid Age

Command Grammar	epon(rstp)# bridge maxage < maxage >
Function	Configure RSTP bridge's maximum valid age which is the valid time for receiving BPDU packet from appointed port's bridge.
< maxage >	Value range : 6-40 ;must demand the following bind relation: $2 \times (\text{ForwardDelay} - 1.0\text{second}) \geq \text{MaxAge}$ MaxAge is bridge infomration's maximum valid time ; ForwardDelay: forward delay

4.3.6.1.3. Bridge Priority

Command Grammar	epon(rstp)# bridge priority <priority >
Function	Set RSTP bridge priority
<priority >	Appointed bridge priority integer value from 1 to 61440,and step length is 4096 ,meaning $4096 \times N$ (N is from 0 to 15) .

4.3.6.2. Enable RSTP Function

Command Grammar	epon(rstp)# enable
Function	Enable switch control module's uplink port 's RSTP function

【Example】

- 1.Enable switch control module's uplink port 's RSTP function

epon(rstp)#enable

4.3.6.3. Disable RSTP Function

Command Grammar	epon(rstp)# disable
Function	disable switch control module's uplink port 's RSTP function

4.3.6.4. Hold Bridge Forwarding Frame Count

Command Grammar	epon(rstp)# hold-count <holdcount>
Function	Configure RSTP's deliving BPDU packet limit and appoint the maximum delivering BPDU packet within 1 second .
<holdcount>	Value range from 1 to 10.

4.3.6.5. Configure RSTP Port Parameter

4.3.6.5.1. Set RSTP's Edge port Management

Command Grammar	epon(rstp)# port <portlist> edgecfg <edge>
Function	Configure RSTP port's managed edge port attribute. Appoint the port whether to be edge port or not .Edge port does not go through "discarding-learning-forwarding " step but transfer to switch status directly .
<portlist>	Appointed port list ,any one from ge1 to ge4 .
<edge>	Configure appointed RSTP port's edge port attribute with byte value such as edge ,non-edge and auto .

4.3.6.5.2. Set RSTP Port's Protocol Version Checkout

Command Grammar	epon(rstp)# port <portlist> mcheck
Function	Configure RSTP port's protocol version check out .When executing this command ,the appointed port's mode is force to be the same as next received BPDU packet version.If the next packet is STP BPDU packet ,the port's mode is STP .If it's RSTP BPDU packet ,the port's mode is RSTP. RSTP port's protocol version is a booting command, not available to preserve the attributed value continually .
<portlist>	Appointed port list ,any one from ge1 to ge4 .

4.3.6.5.3. Set RSTP Port's Point-to-Point Attribution

Command Grammar	epon(rstp)# port <portlist> p2pcfg <p2p>
Function	Configure RSTP port's point to point index . whether the appointed port is point-to-point port.Point to point port could allow to switch to forward status rapidly .Non-point to point port needs to go through step of discarding-learning-forwarding first before switching to forward status .
<portlist>	Port list from ge1 to ge4
<p2p>	Appointed RSTP port index with bytes value such as p2p,shared and auto .

4.3.6.5.4. Set RSTP Port's Link Cost

Command Grammar	epon(rstp)# port <portlist> path-cost <pathcost>
Function	Configure RSTP port's link cost .It's used to calculate the root link's cost .The port with the lowest root link cost will change to forward port when delivering the same bridge ID .
<portlist>	Appointed port list, any one from ge1 to ge4.
<pathcost>	Appointed RSTP port's link cost with integer value from 1 to 200000000.

4.3.6.5.5. Set RSTP Port's Priority Level

Command Grammar	epon(rstp)#rstp port <portlist> priority <priority>
Function	Configure RSTP port's priority level. The port with priority will change to forward port when delivering the same bridge ID and having the same link cost .
<portlist>	Port list ,any one from ge1 to ge4.
<priority>	Configure appointed RSTP port's priority level with integer value valid from 1 to 240 ,step length 16 ,meaning 16xN(n is from 0 to 15) .

4.3.6.6. Show RSTP Configuration Information

Command Grammar	epon(rstp)#show
Function	Show RSTP bridge and port's configuration information

【 Example 】

1.show switch control module's RSTP configuration information :

```
epon(rstp)#show
RSTP Bridge Status:
RSTP Setting          :Disable
Bridge ID [PRI-MAC]   :32768-e0:67:b3:00:63:07
Bridge Hello Time     :2 sec
Bridge Max Age        :20 sec
Bridge Forward Delay  :15 sec
Transmit Hold Count   :6
Root Bridge ID        :0-00:00:00:00:00:00
Root Path Cost        :0

RSTP Port Status:
  PID Mode  Pri  PathCost  EdgeCfg  OperEdge  P2PCfg  OperP2P State
  1  RSTP   128  20000    Auto    Non-Edge  Auto    P2P    LinkDown
  2  RSTP   128  20000    Auto    Non-Edge  Auto    P2P    LinkDown
  3  RSTP   128  20000    Auto    Non-Edge  Auto    P2P    LinkDown
  4  RSTP   128  20000    Auto    Non-Edge  Auto    P2P    LinkDown
```

4.3.7. Configure switch control module's Switching Mode

4.3.7.1. Set Private Vlan Mode

Command Grammar	epon# swmode pve <mode> <net-port>
Function	Configure private vlan mode for uplink port of switch control module
< mode >	Private vlan mode : <disable onebyone trunk>. disable:normal switch mode ,where the uplink port of switch control module doesn't has VLAN limitation . Onebyone: switch control module's uplink port is corresponding with PON port -----corresponding mode ,such as ge1-ge5,ge3-ge6Trunk: port convergence mode
< net-port >	When mode is trunk mode ,that means to converge the uplink ports .port from ge1 to ge4 .

4.3.7.2. Show switch control module's Switch Mode Configuration

Command Grammar	epon# swmode show
Function	Show switch control module's switch mode

【Example】

1. Show switch control module's switch mode configuration information

epon#swmode show	
Current basic switch mode	:vlan-unaware
Current private vlan mode	:disabled

4.3.7.3. Enable switch control module's Vlan Function

Command	epon# swmode vlan <mode>
----------------	---------------------------------

Grammar	
Function	Enable switch control module's Vlan Function
<mode>	aware: eable vlan (vlan aware) unaware: disable vlan (vlan unaware)

4.3.8. Uplink Port Management mode of switch control module

Command Grammar	epon#swport <port>
Function	Enter port management mode of switch control module .under this mode , you can configure several index function.
<port>	Appointed port list ,any one from ge1 to ge6.

【example】

1.Enter switch control module's port 1 management mode

```
epon#swport ge1
epon(ge1)#
```

```
epon(ge1)# ?          input "? "or "help"to show directory :
acc-frame             - set port access frame type
def-pri               - set port default priority
duplex                - set port duplex
[no] enable           - set port enable
flow-ctrl              - set port flow control
ingr-filter            - set port ingress filter
mode                  - set port mode
nest-vlan              - set port nest vlan enable or disable
prot-vlan              - set port protocol based vlan enable or disable
pvid                  - set port pvid
rate-ctrl              - set port ingress rate limit parameters
reautonego            - set port reautonegotiation
show                  - show port attribute information
[no] shutdown         - shut down a port
speed                 - set port speed
```


4.3.8.1. Set Port's RX Frames Types

Command Grammar	epon(ge1)#acc-frame <type>
Function	Set switch control module port's RX packet frame types
<type>	Packet frame types : tagged:receive tagged packet only untagged: receive untagged packet only all:receive all types of packet frame

【Remark】

Our OTL system can't set untagged type mode yet .

4.3.8.2. Set Port's Default Priority Level

Command Grammar	epon(ge1)#def-pri <privalue >
Function	Set switch control module's default priority level ,similar to PVID .When port received untagged vlan packet ,the packet is set by priority .The priority level is port's default 802.1P priority .The data packet will enter different priority queue to receive different service according to corresponding priority level and flow category .
<privalue>	Set configured port's priority level value from 0 to 7

4.3.8.3. Configure Port's Duplex Mode

Command Grammar	epon(ge1)#duplex <duplex >
Function	Set switch control module port's duplex mode
<duplex>	full:full duplex mode half:half duplex mode auto:auto-negotiation mode

4.3.8.4. Enable Port

Command Grammar	epon(ge1)# enable
Function	Enable the switch control module port to deliver and receive packet. Under some circumstance, user can use this function to test the networking performance.

4.3.8.5. Disable Port

Command Grammar	epon(ge1)# no enable
Function	Disable the switch control module port to deliver and receive packet. Under some circumstance, user can use this function to test the networking performance.

4.3.8.6. Configure Port's Flow Control Mode

Command Grammar	epon(ge1)# flow-ctrl <ctrl>
Function	Configure switch control module port's flow control mode. Both optical port mode and electrical mode could support flow control configuration enforcedly and auto-negotiation; Under the half-duplex mode ,the port enable the back flow control function default; Under the full-duplex mode, you can enable or disable flow control in compliant with 802.x standard.
<ctrl>	enable: enable flow control function disable:disable flow control function auto:auto-negotiation mode

4.3.8.7. Set Port's RX Filter Function

Command Grammar	epon(ge1)# ingr-filter <operator>
------------------------	--

Function	Configure switch control module port's RX packet filtering function. When the port is not the vlan member appointed by frame VID ,the packet is dumped at the time of receiving the frame .
<operator>	Enable: enable switch control module port's RX frame filter function Disable: disable switch control module port's RX frame filter function

4.3.8.8. Configure Port Mode

Command Grammar	epon(ge1)# mode <mode>
Function	Configure switch control module port's port mode,including copper and fiber modes .
<mode>	Copper: copper mode fiber :fiber mode

4.3.8.9. Enable Port's Nest-Vlan Function

Command Grammar	epon(ge1)# nest-vlan <operator>
Function	Configure switch control module port's nest vlan function
<operator>	enable :enable port nest's vlan function Disable: disable port nest's vlan function

4.3.8.10. Enable Port's Protocol Vlan

Command Grammar	epon(ge1)# prot-vlan <operator>
Function	Configure switch control module port's protocol vlan function
<operator>	Enable: enable port's protocol vlan function Disable: disable port's protocol vlan function

【Remark】

This command's effect is the same as "[no] enable <portlist>" under the protocol vlan configuration mode .

[4.3.5.6.Enable Port Protocol VLAN Function](#)

[4.3.5.7.Disable Port Protocol Vlan Function](#)**4.3.8.11. Set Port's PVID**

Command Grammar	epon(ge1)# pvid <pvid>
Function	Configure switch control module port's default vlan ID .
<pvid>	Vale range from 0 to 4094

4.3.8.12. Configure Port's Rate Limits**4.3.8.13. Configure Port's Reauto-Negotiation Function**

Command Grammar	epon(ge1)# reautoneg
Function	Configure switch control module port's auto-negotiation function, which is needed on the purpose of networking debugging. This function could be replaced by means of plug in and out of the cable ,but if the cable/fiber is too complicated or too far ,it is better to realize it via software .Therefore ,port configuration management module must provide a command port for reauto-negotiation command ,which doesn't preserve the attributed value continually.

4.3.8.14. Show Port Information

Command Grammar	epon(ge1)# show
Function	Show switch control module port's configuration information

【Example】

1.Show switch control module port 1 's configuration information

epon(ge1)#show			
-----	PortId	2	Attribution -----
Auto-Negotiation:enable	AdminStatus	:	enable

PVID	:1	DefaultPriority	:0
Learning	:enable	AccFrameType	:All
CfgSpeed	:1000M	CfgDuplex	:full
WorkSpeed	:10M	WorkDuplex	:half
CfgFlwCtrl	:disable	LinkStatus	:down
IngressRateCtrlType	:All	IngressRateLimit	:0
EgressRateLimit	:0		
----- End -----			

4.3.8.15. Configure Port's Compulsive Shutdown Function

Command Grammar	epon(ge1)# shutdown
Function	Configure switch control module port's compulsive shutdown function. In an exceptional case, such as attached by virus or hacker and can't take any actions ASAP , the shutdown port function is recommended .

4.3.8.16. Remove Compulsive Shutdown Port

Command Grammar	epon(ge1)# no shutdown
Function	Remove switch control module port's compulsive shutdown function. In an exceptional case, such as attached by virus or hacker and can't take any actions ASAP , the shutdown port function is recommended .

4.3.8.17. Configure Current Port Rate

Command Grammar	epon(ge1)# speed <speed>
Function	Configure switch control module port's speed.Under fiber port mode ,the port could only work at the speed of 1000Mbps;Under the copper port mode ,the port can work at different speed and available for auto-negotiation function configuration .
<speed>	10m: 10mbps

	100m: 100mbps 1g: 1gbmp(1000mbps) 10g: 10gbps Auto: auto-negotiation
--	---

4.3.9. System Configuration Mode

Command Grammar	epon# system
Function	Enter EPON system's management mode

【Example】

1. Enter system management mode

epon#system epon(sys)#

epon(sys)# ?	input "?" or "help" to show current directory
cfg-sync	- synchronize onu config with its config file
console	- configure console parameters
onu-auth	- configure ONU authentication parameters
read-comm	- set snmp read community string
reboot	- reboot the system
restore	- restore to saved configuration
save	- save system configuration
trap-addr	- set trap destination IP address
write-comm	- set snmp write community string

4.3.10. Synchrony with ONU Configuration

Command Grammar	epon(sys)# cfg-sync <slot> <status>
Function	Configure OLT's setting is synchronous with ONU configuration. When this function is enabled , ONU will remove its own nvs automatically before ONU authorized to OLT .All configuration under the ONU will be cleared .All ONU's configuration is valid after authorized under the OLT .
<slot>	PON card slot with integer value from 1 to 4 .

<timeout>	Optional index:<enable disable>.
------------------------	----------------------------------

【Remark】

This function default is close because enabling it will make ONU's saved configuration lost ,needing to configure it again undet the OLT .Please use this function properly .

4.3.10.1. Backup EPON System Configuration

Command Grammar	epon(sys)# config backup <host>
Function	Put all EPON sytems's configuration file backup to TFTP server.
<host>	Appointed TFTP server's IP address

4.3.10.2. Restore EPON System Configuration

Command Grammar	epon(sys)# config upgrade <host>
Function	Download system's configuration file from TFTP server and restore EPON system's configuration.
<host>	Appointed TFTP server's IP address

4.3.10.3. Configure Console Port Speed

Command Grammar	e pon(sys)# console speed <speed>
Function	Set OLT system's console port speed
<speed>	Value range:bps2400-bps115200. Remark: value should be 2400*2^n (n is integer)

4.3.10.4. ONU Authorization Management Mode

Command Grammar	epon(sys)# onu-auth
Function	Enter onu authorization management mode

【Example】

1. enter onu authorization management mode

```
epon(sys)#onu-auth
epon(sys-onuauth)#
```

epon(sys-onuauth)# ? input “ ? ” or “ help ” to show directory:

- inv-onu** - process invalid ONU list
- list** - configure ONU address range
- type** - set authentication type

4.3.10.4.1. Illegal ONU List Operation

4.3.10.4.1.1. Clear Illegal ONU List

Command Grammar	epon(sys-onuauth)# inv-onu clear
Function	Clear current illegal ONU list ,then the illegal onu can get a new chance to be authorized under OLT .

4.3.10.4.1.2. Show Illegal ONU List

Command Grammar	epon(sys-onuauth)# inv-onu show
Function	Show illegal ONU list and list all illegal ONU’s MAC address

4.3.10.4.2. Configure ONU Authorized Address List

4.3.10.4.2.1. Add ONU Authorized Address List

Command	epon(sys-onuauth)# list add <start> <end> <type>
----------------	---

Grammar	
Function	Add an ONU address list and appoint its authorization type
<start>	ONU starting MAC address: such as 00:A1:02:02:01:B0
<end>	ONU ending MAC address: such as:00:A1:02:02:01:F0
<type>	Set onu authorization type under address list with following value: Blacklist: the ONU with this type of MAC address can't be authorized to OLT . Whitelist: the onu beyond this MAC address range can't be authorized .

【Example】

1.Add the ONU with the MAC address : 00:A1:02:01:12:B0 to the blacklist

```
epon(sys-onuauth)#list add 00:A1:02:01:12:B0 blacklist
```

4.3.10.4.2.2. Delete ONU Authorized Address List

Command Grammar	epon(sys-onuauth)# list delete <index>
Function	Delete an ONU address list
<index>	MAC address list index

4.3.10.4.2.3. Show Current MAC Address List

Command Grammar	epon(sys-onuauth)# list show
Function	Show current ONU authorized address list and distribute an index directory for all the MAC address automatically

【Example】

1.Show current ONU authorized MAC address list:

```
epon(sys-onuauth)#list show
```

NO.	Start Address	End Address	Type
1	00:a1:02:01:12:b0	00:a1:02:01:12:b0	blacklist

4.3.10.4.3. Configure ONU Authorized Type

Command Grammar	epon(sys-onuauth)# type <type>
Function	Set EPON system ONU's authorized type
<type>	Valid value:<blacklist whitelist none>. Blacklist: All onu in the MAC address type can't be authorized . Whitelist: All ONU beyond the MAC address type can't be authorized. None: non-authorization ,all ONU could be authorized .

4.3.10.5. Set SNMP Read Community

Command Grammar	epon(sys)# read-comm <community>
Function	Set EMS software SNMP's read community
< community >	Read community with bytes serial ,the longest length couldn't be over 26 bytes ,such as public .

4.3.10.6. Reboot OLT

Command Grammar	epon(sys)# reboot <device> <slot> <olt> <onu>
Function	Reboot EPON device;This command will reboot switch control module , some PON card ,some ONU or the equipment under the EPON system . Input command " reboot " will only reboot the switch control module .
<device>	Appoint the device to be rebooted with following index: ctrl-card: reboot switch control module <slot><olt> <onu> is ignored . pon-card :reboot appointed pon card with index <slot> <olt> <onu> is ignored . Onu:reboot appointed onu under the index <slot> <olt> <onu> all : reboot the whole EPON system including OLT and ONU .

	<slot><olt> <onu> is ignored.
<slot>	Appoint PON card's slot number with valid value from 1 to 4 .
<olt>	Appoint PON port number under a pon card slot with valid value from 1 to 2 .
<onu>	Appoint ONU number with valid value from 1 to 64 .

【Example】

1.Reboot switch control module

```
epon(sys)#reboot
```

Or

3.Reboot the whole EPON system including switch control module ,all online PON card and all online ONU)

```
epon(sys)#reboot all
```

4.3.10.7. Restore Default Configuration and Reboot Equipment

Command Grammar	epon(sys)# restore <device> <slot> <olt> <onu>
Function	Restore ex-factory default configuration and reboot the device . When <device> <slot> <olt> <onu> is ignord ,the command just restore switch control module configuration .
<device>	Appoint the device to restore default configuration with valid index : ctrl-card: restore switch control module's default configuration <slot><olt> <onu> is ignored pon-card: restore appointed PON card under <slot> configuration <olt> <onu> is ignored. onu :restore default configuration for appointed onu with index : <slot> <olt> <onu> all: restore system's all default configuration and command <slot><olt> <onu> is ignored .
<slot>	Appoint PON card's slot number with valid value from 1 to 4 .
<olt>	Appoint PON port number with valid value from 1 to 2 .
<onu>	Appoint ONU number with valid value from 1 to 64 .

4.3.10.8. Save Current Configuration

Command Grammar	epon(sys)# save <device> <slot> <olt> <onu>
Function	Save current configuration. Just input “ save “ command to save the switch control module’s current configuration .
<device>	Appoint the device to save current configuration with valid index : ctrl-card: save switch control module’s current configuration <slot><olt> <onu> is ignored pon-card: save appointed PON card under <slot> configuration <olt> <onu> is ignored. onu :save configuration for appointed onu with index : <slot> <olt> <onu> all: save system’s all default configuration and command <slot><olt> <onu> is ignored .
<slot>	Appoint PON card slot number with valid value from 1 to 4 .
<olt>	Appoint PON port number with valid value from 1 to 2 .
<onu>	Appoint ONU number with valid value from 1 to 64 .

4.3.10.9. Set Trap Receiving IP Address

Command Grammar	epon(sys)# trap-addr <index> <ip-addr>
Function	Configure EPON’s receiving trap IP address with 4 IP at most.
<index>	Trap receiving IP index with valid value from 1 to 4 .
<ip-addr>	Set trap receiving IP address ,such as 192.168.0.1.

4.3.10.10. Set SNMP Written Community

Command Grammar	epon(sys)# write-comm <community>
------------------------	--

Function	Set SNMP's written community of EMS software
< community >	Written community with bytes serial ,longest length 26 bytes ,such as : private .

4.3.11. Trunk Management Mode

Command Grammar	epon#trunk <trunkid>
Function	Create a trunk group and enter the trunk management mode for configuration .
< trunkid >	Trunk number with valid value from 1 to 4

【Example】

- 1.Create trunk 1 and enter trunk 1's management mode

epon#trunk 1 epon(trunk1)#

epon(trunk1)# ? input "? "or"help"to show current directory

- balance-algorithm** - set trunk balance algorithm
- delete** - delete the specifically trunk
- member** - Set trunk member

4.3.11.1. Configure Trunk Balance Algorithm

Command Grammar	epon(trunk1)#balance-algorithm < balance>
Function	Configure trunk's balance algorithm.All balance algorithm is the same when all trunk group adopts the same balance algorithm. Trunk group's packet can be shared among trunk member poprts .EPON system support several balance algorithm ,such as based on MAC address ,IP address ,transmission port number, MAC+IP, MAC+ transmission port number
<balance >	Trunk algorithm with valid index : mac :based on MAC address's KE balance algorithm. Ip: based on IP address's balance algorithm

	l4port: based on transmission port's balance algorithm ip-mac: based on MAC+IP address's balance algorithm l4port-mac inl2if :based on packet receiving port's balance algorithm
--	---

4.3.11.2. Delete Trunk Group

Command Grammar	epon(trunk1)# delete
Function	Delete trunk group and its member

4.3.11.3. Add Trunk Member

Command Grammar	epon(trunk1)# member <portlist>
Function	Add trunk group's member port
<portlist>	Appoint trunk member port list from ge1 to ge8

【Example】

- 1.Add member port ge1,ge3,ge4 and ge8 to trunk 1 .

epon(trunk1)#member ge1,ge3-ge4,ge8

4.3.12. Show Trunk Configuration Information

Command Grammar	epon# show trunk
Function	Show switch control module's current trunk configuration

4.3.13. User Management

4.3.13.1. Set User Authority

Command Grammar	epon# user access <i><name></i> <i><access ></i>
Function	Change appointed user's priority mode to limit use to access to system or limit the user right .
<i><name></i>	Appointed user name under the priority mode with the length from 4 to 15 bytes.
<i><access></i>	admin : manager who has all the configuration and operation rights . Guest: guest who could only ready the operation. Configuration

【Remark】

Only the system administrator has the rights to change the system user's priority.

4.3.13.2. Add User

Command Grammar	epon# user add <i><name></i> <i><passwd></i> <i><access ></i>
Function	Add a user
<i><name></i>	User name with the length from 4 to 15 bytes.
<i><passwd></i>	Optional index to change new password .if there is no index ,the user's password is blank ;if index is provided ,it could be any obvious bytes combination with the length from 6 to 31 bytes .
<i><access></i>	admin : administrator who has all the configuration and operation rights . Guest: guest who could only ready the operation. Configuration

4.3.13.3. Delete User

Command Grammar	epon# user delete <i><name></i>
Function	Delete appointed user from logging in the system

<name>	Appoint the user name to be deleted with the bytes length from 4 to 15
---------------------	--

【Remark】

Only the system's administrator(the user priority level is 1) has the rights to add and delete system users .

4.3.13.4. Change User Password

Command Grammar	epon# user passwd <name> [<password>]
Function	Change appointed user's log in password . If <password> is ignored , the log in password is blank.
<name>	User name with the bytes length from 4 to 15 bytes .
<password>	Optional index to input new password . If the index is not provided ,the password is blank ;if the index is provided ,the password length can be from 6 to 31 bytes.

4.3.13.5. Show Current User's Information

Command Grammar	epon# user show
Function	Show system's all user list

【Example】**1.Show System's Current User List**

epon#user show		
User: admin	Access: administrator 0	Timeout: 1800
User: guest	Access: guest 0	Timeout: 600

4.3.13.6. Change User's Timeout

Command	epon# user timeout <name> <timeout>
----------------	--

Grammar	
Function	Change appointed user's timeout time. Within the timeout time ,user can't make any operation and log out the system automatically.
<name>	Change timeout user name with the byte length from 4 to 15 bytes.
<timeout>	Appointed user's timeout time with the valid index range from 1to 3600 and unit is second.

【Remark】

Change user's timeout function ,which is valid after logging in the system again .

4.3.14. VLAN Management Mode

Command Grammar	epon# vlan <vlanid>
Function	Create a vlan and enter vlan management mode for configuration .
< vlanid >	Vlan ID to be modified or created with valid value from 1 to 4094.

【Example】

1.Create Vlan100 and enter vlan100's management mode

```
epon#vlan 100
epon(vlan100)#
```

epon(vlan100)# ? input“? ”or “help” to show current directory:
delete - delete vlan members or vlan
member - add vlan member

4.3.14.1. Delete Vlan Member

Command Grammar	epon(vlan100)# delete member <portlist>
Function	Delete vlan member port. Input “delete member” to to delete this vlan and member port.
<portlistt>	Appoint vlan member port list ,any port from ge1 to ge16.

4.3.14.2. Delete Vlan

Command Grammar	epon(vlan100)# delete
Function	Delete current vlan and all member ports under this vlan.

4.3.14.3. Add Vlan Member Port list

Command Grammar	epon(vlan100)# member <portlist> <tag>
Function	Add vlan member port and set its tag mode.
<portlistt>	Added vlan member port list ,from ge1 to ge16.
<tag>	Tag mode with fixed index “tag” . When the member port is marked with tag .The packet from the port is added with vlan tag . When tag is deleted ,this port is not marked with tag .

【Example】

1.add switch control module port ge1,ge2,ge3 with vlan 100 to the tag member ports ,while port ge4,ge5,ge16 are member ports with vlan100 without tag .

```
epon(vlan100)#member ge1-ge3 tag
epon(vlan100)#member ge4-ge5,ge16
```

4.3.15. Show Vlan Configuration Information

Command Grammar	epon# show vlan
Function	Show switch control module’s vlan configuration information .

【Example】

1.Show switch control module’s valn configuration:

```
epon#show vlan
vlan 1:
```

```
tagged ports    :  
untagged ports :ge1-ge16  
vlan 100:  
tagged ports   :ge1-ge3  
untagged ports :ge4-ge5,ge16
```

4.4. Show System Running Information

4.4.1. Show System's Current CPU Running Status

Command Grammar	epon>show cpu
Function	Show system's CPU running status information

【Example】

1.Show system's CPU Running Information:

```
epon>show cpu
```

NAME	ENTRY	TID	PRI	total % (ticks)	delta % (ticks)
tJobTask	0xd19a4	0x8ac158	0	0% (0)	0% (0)
mTrAging	0x43975c	0xf7c350	5	0% (0)	0% (0)
tErfTask	0xb46bc	0x8b5a30	10	0% (0)	0% (0)
intSched0	0x31a72c	0xf0b5e0	10	0% (0)	0% (0)
intSched1	0x31a72c	0xf16880	10	0% (0)	0% (0)
tNetTask	0x363c0	0x945d00	40	0% (0)	0% (0)
tlbcpPoll	0x13dc7c	0x1243cd0	45	0% (0)	0% (0)
tlbcpRx	0x13e74c	0x1241338	46	13% (2)	13% (2)
tXbdService	0xccba0	0xa1af80	50	0% (0)	0% (0)
tFtp6d	0x2f97c	0xa16ef0	56	0% (0)	0% (0)
tUserLog	0x16a9c0	0xf826a8	60	0% (0)	0% (0)
tUpgradeTask	0x167174	0x1348aa8	64	0% (0)	0% (0)
KERNEL				0% (0)	0% (0)
INTERRUPT				0% (0)	0% (0)
IDLE				86% (13)	86% (13)
TOTAL				99% (15)	99% (15)

4.4.2. Show System's Memory Use Status

Command Grammar	epon>show mem
Function	Show system's memory use status information

【Example】

1.Show system's current memory user information:

status	bytes	blocks	avg block	max block

current				
free	12695080	4	3173770	12681624
alloc	12055336	1185	10173	-
internal	408	2	204	-
cumulative				
alloc	12702512	1795	7076	-
peak				
alloc	12059424	-	-	-

4.4.3.Show System's Task Status

Command Grammar	epon>show task
Function	Show system's current task information

4.4.4.Enable CATV (RF) Function

Current ,C-Data has developed and produced a wide range of ONU models ,such as only data ONU FD101H,FD111H,FD112H,FD104H,FD104B,FD108B ,and ONU of various service function, such as FD304H(4FE+RF),FD204H(4FE+2POTS_ ,FD404H(4FE+2POTS+RF).So far ,our EMS and CLI NMS could both support data and RF-cutoff function in our EMS or in our CLI management interface. As for VOIP function, we could only support CLI management on the console port of the ONU .

Command Grammar	epon(slot3-olt2-onu9)#catv enable
Function	Enable ONU's RF function

4.4.5.disable CATV (RF) Cut-Off Function

Command Grammar	epon(slot3-olt2-onu9)#catv disable
Function	Disable ONU's RF function if subscriber don't pay CATV cost on time from the OLT management interface .

4.5. Global Command

Global command can be used under any command mode.

4.5.1.Create Command Alias

Command Grammar	alias <alias> <cmd>
Function	Create appointed command's alias
<alias>	Input command's alias
<cmd>	Original command

4.5.2.Change Directory

Command Grammar	cd <directory>
Function	Enter appointed directory
<directory>	Input directory

4.5.3.Clear Screen

Command Grammar	clear
Function	Clear screen

4.5.4.Copy File

Command Grammar	<code>copy <scr-file> <dest-file></code>
Function	Copy file ; When <dest-file> is ignored , <scr-file> 's contents is printed on the screen.
< scr-file >	Source file
<dest-file>	destined file

4.5.5.Show System's Date

Command Grammar	<code>date</code>
Function	Show system's current date and time .

4.5.6.Delete File

Command Grammar	<code>del <filename></code>
Function	Delete appointed file
< filename >	Appoint deleted file name

4.5.7.Exit From The Current Command Mode

Command Grammar	<code>exit</code>
Function	Exit from the current command mode and return to the previous command mode .

4.5.8. Return to System Main Directory

Command Grammar	<code>end</code>
Function	Return to the system's main directory

4.5.9. Help

Command Grammar	<code>help</code>
Function	Command help

4.5.10. Command History

Command Grammar	<code>history</code>
Function	Show current input command history

4.5.11. Log Out System

Command Grammar	<code>logout</code>
Function	Log out system.

4.5.12. Show Current File List

Command Grammar	<code>ls</code>
Function	Show current directory's file list

4.5.13. PING

Command Grammar	<code>ping <host></code>
Function	Test remote host's connection
< host >	Remote host's ip address

4.5.14. Show Directory Route

Command Grammar	<code>pwd</code>
Function	Show directory route

4.5.15. TFTP

Command Grammar	<code>tftp <cmd> <filename> <mode></code>
Function	Upload/download file through TFTP
< cmd >	TFTP command: get : download file Put: upload file
<filename>	File name
<mode>	File format : ascii file format binary format